

# KPR2000

**SINGLE ENTRY ACCESS CONTROL  
KEYPAD AND PROXIMITY READER**



## Multifunction Control in an Attractive, Inconspicuous Device

LiftMaster's KPR2000 is a feature-rich Keypad and Proximity Card Reader Access Controller that is simple to install and looks great, making it an excellent choice for both Residential and Commercial applications.

A secure and vandal-resistant enclosure with a gray powder-coated finish creates an upscale and stylish appearance. Cool blue backlighting of the keys assures day or night visibility.

The KPR2000 supports a maximum of 2,000 users in multiple access configurations (Card Only, Card or 4 to 6 Digit PIN, or Card + PIN). Supports HID 26 and 30-bit Wiegand proximity card formats.

Install the KPR2000 on a LiftMaster® pedestal and pair it with a LiftMaster® gate or commercial door operator for a superior total entry control solution.



**KPR2000**

## Complete Single Entry Access Device

- Keypad & Proximity Card Reader in One
- Stand-Alone or Wiegand Pass-Through
- 2,000 Users Maximum
  - Card
  - PIN
  - Card and PIN
- Multicolor LED Status Display and Backlit Keypad
- Advanced Programming Features Including Block Enrollment and Adjustable Relay Output Time
- 10 Panic Card/PIN Codes (opens the entry and sets off the alarm)
- Latch made to hold door/gate open

**LiftMaster®**

# KPR2000

## SINGLE ENTRY ACCESS CONTROL KEYPAD AND PROXIMITY READER

### Standard Features

- Single Entry Access Control
- Stand-Alone Controller and Pass-Through Mode (HID Wiegand Proximity and ASCII Keypad)
- Controls Access for up to 2,000 Users (Card Only, Card or PIN, Card and PIN)
- Integrated Alarm Buzzer & Output
- Rugged Vandal-Resistant Backlit Metal Enclosure
- One Programmable Relay Output
- Latch Mode to Hold Door/Gate Open
- Supports Second Keypad Configuration for In and Out Same Door or Gate

### Enhanced Features

- Block Enrollment Capability
- Program Cards Included for Rapid Programming
- Panic Codes (activates relay and sets off the alarm)
- Anti-Tamper Alarm

### Specifications

#### Operating Voltage

12-24VDC

#### Current Draw

≤ 25mA idle; 60mA peak

#### Proximity Card Reader

HID 26 and 30-bit Wiegand Format

#### Onboard Radio

Industry standard 125 kHz

#### Read Range - Proximity

1 inch – 2.5 inch

#### Relay Output Load

2 Amps

#### Alarm Output Load

2 Amps

#### Relay Timer

1-99 seconds

#### Alarm Timer

1-3 minutes

#### Weatherization

Meets or exceeds IP68

#### Operating Temp

-20 to 60 deg C, or -4 to 140 deg F

#### Operating Humidity

10% to 90% Non-condensing

#### Physical

Zinc-alloy enclosure

- Dimensions

5 inch x 3.2 inch x 1.1 inch

- Unit Weight

1.3 lbs

- Shipping Weight

1.5 lbs

### Accessories

Description	Model Number
Low-Profile Access Pedestal	PEDS44
4x4 Pedestal Adaptor	PEDAD
12VDC, 2 Amp Power Supply	PS12D2A
HID 30-bit proximity card, facility code 2	SNACPH32
HID 30-bit proximity card, facility code 9	SNACPH39
HID 30-bit proximity card, ISO Graphics, facility code 2	SNACPHISO32
HID 30-bit proximity card, ISO Graphics, facility code 9	SNACPHISO39
HID 30-bit proximity key, facility code 2	SNACPKH32
HID 30-bit proximity key, facility code 9	SNACPKH39

### Dimensions



# LiftMaster®

The Chamberlain Group, Inc. • 845 Larch Avenue • Elmhurst, IL 60126

[LiftMaster.com](http://LiftMaster.com)



Follow us on Facebook, Twitter

©2013 The Chamberlain Group, Inc. LMTECAKPR2 Printed in U.S.A. 5/13

